



# NORDIC CLASSIC





Åre, Sweden



WC interior



Örebro, Sweden



Tank cabin interior



Saltsjöbaden Golf Club, Sweden



Nora Golf Club, Sweden

# NORDIC CLASSIC

---

## – Toilet cabin with exterior cladding

The Nordic Classic is delivered with a built-in waste tank, or can be delivered for connections to the main water and sewage system. Versatile in design it can be installed in almost any surrounding as its walls are insulated for year-round use. The Nordic Classic can easily be transported and relocated to provide hygiene facilities even in remote locations.

Public transport stops, golf courses, ski resorts, beaches and camping sites, sports facilities, marinas, open-air recreation areas, hiking routes, parks and parking lots are some example where the Nordic Classic is suitable.

## TECHNICAL INFORMATION

---

### – General information

Optional external colour. Timber like cladding with corners and linings made of wood. Fibre glass reinforced plastic roof with inset lighting. Door in the same material as the walls.

### – Equipment

Complete electrical installation for lighting and heating fan. The cabins are equipped with GFCI (Ground Fault Circuit Interrupter) and 3-pole mains inlet for connection to 1-phase 240V/16A electrical outlet. The equipment includes washbasin with tap, electric radiator, waste paper basket, toilet paper holder, clothes hook, mirror and locking device.

### – Ventilation

Manually operated disk valves for natural ventilation. The waste tank is separately ventilated via a waste ventilation pipe.

### – Waste Tank Model

The floor and toilet seat cast in one piece of fibre glass reinforced plastic. 25 litre fresh water container for hand wash purposes. The waste tank is made of rotation cast plastic which is resistant to heat/cold and mechanical effect. The tank forms a separate unit integrated in the toilet building. Water and sanitation liquid to be poured into the tank. The waste tank holds 500 litres (approx. 1600 visits). Requires occasional drainage by sludge suction.

### – WC Model

Floor mounted ceramic toilet pan. For a Ø15 mm (½") incoming fresh water supply connection and Ø 110 mm waste water connection.

### – Sanitation Liquid OdourLess

The OdourLess Sanitation Liquid, or similar product, efficiently removes bad odours and decomposes the waste naturally. The OdourLess Sanitation Liquid is approved by the Swedish National Chemicals Inspectorate with Reg. No. 3958. Efficacious component: potassium nitrate (42%).

#### Dimensions WC Model

Height incl./excl. roof	Width	Depth
2700 mm/2350 mm	1250 mm	1420 mm

#### Dimensions Waste Tank Model

Height incl./excl. roof	Width	Depth
3000 mm/2650 mm	1250 mm	1490 mm

#### Weight

410 kg

#### Weight

430 kg